





COMBAT MODELS	COMBAT CAMO WORKS			COMBAT ICE HELL	COMBAT TITANIUM R
ENGINE	2 stroke engine			2 stroke engine	2 stroke engine
ENGINE CAPACITY	2	250cc EFI 300cc EFI		250cc EFI 300cc EFI	250cc EFI 300cc EFI
POWER 25 HP / 9		9200 rpm 31 HP / 9200rpm	25	5 HP / 9200 rpm 31 HP / 9200rpm	25 HP / 9200 rpm 31 HP / 9200rpm
TORQUE 4,0 Kg.m / 4		4500 rpm 4.9 Kg.m / 4500 rpm	4,0 K	(g.m / 4500 rpm 4.9 Kg.m / 4500 rpm	4,0 Kg.m / 4500 rpm 4.9 Kg.m / 4500 rpm
GEARBOX ^{6 speed gear,}		4 gear trials developed, each one ECU controlled	6 spee	d gear, 4 gear trials developed, each one ECU controlled	6 speed gear, 4 gear trials developed, each one ECU controlled
CLUTCH		Oil wet multidisc			
RADIATOR		Vertigo design, adapted to frame shape			
ECU ENGINE CONTROL UNIT		Vertigo design, controlling: gear position, engine temperature, pressure, fuel pump water pump, electronic timming			
ENGINE CONTROL SENSORS		Integrated injection driver			
ENGINE CONTROL SENSORS		Integrated starter driver			
ENGINE CONTROL SENSORS		Barrel gear sensor, can control each engaged gear			
ENGINE CONTROL SENSORS		Protocal can 2.0 B			
ENGINE CONTROL SENSORS		Crankshaft position sensor			
ENGINE CONTROL SENSORS		PWM pump water control			
ENGINE CONTROL SENSORS		Engine fan control sensor			
BATTERY		Small battery ultra capacitors			
POWERBOX ECU		Vertigo design, controls all the electircal power, protects all the components from short circuit			
POWERBOX ECU		Vertigo design, controls all the electircal power, protects all the components from short circuit			
MANIFOLD				Stainless steel	
WEIGHT		69kg		68kg	65kg
SWING ARM		Cast aluminium pivot points, 2 piv swing arm	ot point	Cast aluminium pivot points, 2 pivot poir swing arm	Magnesium 2 pivot point swing arm
FRONT SUSPENSION		Tech Alu Black		Tech Alu Gold	Tech Alu Gold
REAR SUSPENSION		Mono shock/swing arm, Vertigo swing arm combined with REIG monoshock with rebound adjust	GER	Mono shock/swing arm, Vertigo design swing arm combined with REIGER monoshock with compression + reboun adjustment	swing arm combined with REIGER
MUDGUARDS		Double injection, PPR/TPR combined components			
AIRBOX		1,1l capacity upper position airbox			
FUEL TANK		2,71I capacity, low and centre of gravity position			
EXHAUST SILENCER		Aluminium central position - protected from damage			
HANDLEBAR		Vertigo Renthal Renthal			Renthal
RIM		Morad			
CRANKCASE		Aluminium		Aluminium	Magnesium
REAR SPINDLE		Standard chain adjustment	t	Single action snail-cam chain adjustmen	Single action snail-cam chain adjustment